



DECLARATION OF PERFORMANCE

DOP Ref: Aggregate Concrete Masonry Unit (GPLM) – 10.4 (440x140x215) Solid

- 1. Unique Identification code of Product type**
Aggregate Concrete Masonry Unit – 10.4 (440 x 140 x 215) Solid
- 2. Type, Batch or Serial Number or any other Element allowing identification of the Product**
See Point 1
- 3. Intended use or uses of the product, in accordance with the applicable harmonized technical specification**


For use in the construction of load bearing and non-loadbearing solid internal and external walls, above and below the damp proof course and the inner and outer leaves of cavity walls
- 4. Name and registered address of manufacturer**
Quinn Building Products, 235 Ballyconnell Road, Derrylin, Co. Fermanagh, Northern Ireland, BT92 9GP
- 5. Where applicable, name and contact address of the authorised representative whose mandate covers tasks specified in Article 12(2):**
Not Applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**
System 2+
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**
The notified product certification body, British Standards Institution (Notified Body reference no. 0086) has performed the initial inspection of the manufacturing plant and of factory production control, the continuous surveillance, assessment and evaluation of factory production control before placing the product on the market under system 2+ and issued the certificate of constancy of performance.
- 8. Declared Performance**
Refer to table attached
- 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

QUINN CONCRETE



DECLARATION OF PERFORMANCE

Quinn Building Products 235 Ballyconnell Road, Derrylin, Co. Fermanagh, Northern Ireland, BT92 9GP		
EN 771-3:2011+A1:2015 Specification for masonry units – Part 3: Aggregate Concrete Masonry Units		
13 0086-CPR-597548		
Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions <i>mm</i>	Length	440
	Width	140
	Height	215
Configuration	Solid Group 1(See below)	BS EN 771-3:2011+A1:2015
Dimensional Tolerances	GPLM	
Compressive Strength unit category	I	
Mean Compressive Strength N/mm^2	10.4	
Dimensional Stability (Shrinkage) mm/m	0.6	
Shear Bond Strength N/mm^2	0.15 (Annex C BS EN 998-2)	
Flexural Bond Strength N/mm^2	NPD	
Reaction to Fire	Euroclass A1	
Water Absorption $g/m^2s^{0.5}$	NPD	
Water Vapour Diffusion coefficient μ	5/15 (Tabulated values BS EN 1745)	
Durability against freeze thaw	NPD	
Gross Dry Density Kg/m^3	1900	
Thermal Conductivity $W/m.k$	1.09 ($\lambda_{10,dry}$)	
Dangerous Substances	See footnote	
Note: Information on dangerous substances will only be given when and where required in the appropriate form. See Annex ZA.3 of BS EN 771-4:2011		

Configuration on edge



Configuration on flat



Authorised by: Liam McCaffrey
 Position: CEO
 Date of Issue: 23rd May 2016