

QUINN THERM

DECLARATION OF PERFORMANCE



DOP Number: 007a/013

Designation Code: PIR-EN 13165- T2-W2-L2-DS(TH)4-DS(-20)2-WL(T)2-CS(10/Y)150

- Unique Identification code of Product type**
Quinn Therm QRFR-FFR - Foil Faced Flat Roof Board
- Type, Batch or Serial Number or any other Element allowing identification of the Product**
Foil Faced Flat Roof 25 -55mm. PIR Rigid insulation board with Gastight Aluminum Facings.
- Intended use or uses of the product, in accordance with the applicable harmonized technical specification**
PIR Thermal Insulation board for the construction Industry
- Name and registered address of manufacturer**
Quinn Therm Ltd,
Scotchtown,
Ballyconnell,
Co Cavan,
Ireland
- System or systems and verification of constancy of performance of the product as set out in**
AVCP System 3
- Covered by harmonised standard**
EN 13165
- Name and address of the notified bodies determining product-type on the basis of type testing**

BRE Global, Bucknalls Lane, Watford, Herts, WD259XX, UK	British Bord of Agrément, PO Box 195, Bucknalls Lane, Garston, Herts WD2598A, UK.
--	---
- Notified Testing Laboratory Number**

BRE Test No: 0832	Notified Testing Laboratory Number BBA Test No: 0836
-------------------	---

QUINN THERM

DECLARATION OF PERFORMANCE

9. Declared Performances

Essential Characteristic	Performance		Harmonised Technical Specification
Reaction to Fire	Euro Class F		EN 13165
Reaction to Fire in Use	B _{Roof} (t ₄)		
Thermal Resistance	RD ((m ² .K)/W)		
	d ^N 25mm = 1.13 d ^N 30mm = 1.36 d ^N 50mm = 2.27 d ^N 5 mm = 2.5		
Thermal Conductivity	W/mK		
	0.022		
Compressive Strength	kPa		
	CS (10\Y)150		
Water Permeability			
	WL(T)2		
Length & Width	mm	1200 x 600 2400 x 200	
	L2&W2 <1000 mm: ±4mm 1000 to 2000mm: ±5mm 2001 to 4000mm : ± 8mm >4000mm: ± 12mm		
Thickness	d ^N		
	25mm – 55mm T ₂		
Squareness	mm/m		
	S _b <= 5		
Flatness	mm	Length ≤ 2.50mm Area ≤ 0.75m ² : deviation ≤ 5mm Area > 0.75m ² : deviation ≤ 10mm	
Release of Dangerous substances	No harmonised test method available		
Flexural Strength	NPD		
Tensile Strength Perpendicular to Faces	NPD		
Durability of reaction to fire against heat, weathering, aging/ degradation	Reaction to Fire does not change over time		
Dimensional stability under specified temperature and humidity conditions	DS(TH)4 & DS(-20,-)2		

10 The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Name and position held by the person empowered to sign the declaration on behalf of the manufacturer.



Liam McCaffrey CEO
16th May 2016